

GLASS DOOR MERCHANDISERS

PRO-KOLD



VC-49



VC-23

- Digital temperature control
- 220 LUX LED display brightness
- Full glass door with energy efficient Low-E glass
- Electronic fan motor and high-quality components
- Energy efficient and low utility costs
- 115v/ 60 Hz

MODELS	Exterior Dimensions	Internal Dimensions	Net Weight	Shelves	Energy Consumption	Compressor Power
VC-12	W: 24 7/8" D: 23 1/4" H: 60 7/8"	W: 21 7/8" D: 18 7/8" H: 49 7/8"	183 Lbs	4	1.464 kwh/24h	1/6 HP
VC-23	W: 29 1/2" D: 25 1/2" H: 78 5/8"	W: 25 1/2" D: 21 5/8" H: 60 1/2"	248 Lbs	4	1.820 kwh/24h	1/4 HP
VC-43	W: 47 3/8" D: 30 3/8" H: 78 5/8"	W: 43 1/8" D: 21 3/4" H: 59 5/8"	430.78 Lbs	8	3.123 kwh/24h	1/2 HP
VC-49	W: 54 1/8" D: 29 3/4" H: 78 5/8"	W: 50" D: 24 7/8" H: 59 5/8"	466.2 Lbs	8	3.290 kwh/24h	3/4 HP

VERTICAL DISPLAY FREEZER

- Intelligent temperature control, reduces and optimizes energy consumption.
- Adjustable shelves to fit your display needs
- LED lights for enhanced product display
- Stainless steel floor
- Automatic defrost cycle



DURF 16W



DURF 32W

MODELS	Exterior Dimensions	Internal Dimensions	Net Weight	Shelves	Energy Consumption	Compressor Power
DURF 16W	W: 30.2" D: 28" H: 78.4"	W: 26" D: 21.5" H: 52"	366 Lbs	4	14.27 kwh/24h	1/2 HP
DURF 32W	W: 54.3" D: 30" H: 78.7"	W: 50" D: 22" H: 52"	485 Lbs	8	17.14 kwh/24h	1 1/4 HP

✓ CUSTOMER SERVICE & WARRANTY:

- Comprehensive service coverage in the continental US.
- Certified technicians and tech support ready to enhance your experience.
- Parts available on our nationwide distribution network.
- 2 years parts and labor warranty coverage + 3 additional years on the compressor.

WELCOME TO THE WORLD OF

PRO-KOLD



1293 N. Post Oak Road, Suite 100 Houston, TX 77055 713.691.1195

DELI CASES

- Digital temperature control
- Three display levels with two levels of fully adjustable shelves
- Corrosion-resistant, stainless steel floor, countertop
- Gravity coil cooling allows for wider range of product to be displayed (deli & pastry)
- Casters included
- Temperature range of 36°F - 41°F
- UL, CSA and NSF Compliant

DDC 40 W



DDC 60 B



DDC 80 SS



MODELS	Exterior Dimensions	Capacity	Shelves	Compressor Power	Available Colors
DDC 40 W	W: 40" D: 35.8" H: 50"	14 ft3	2	1/4 HP	White, Black, Stainless Steel
DDC 60 B	W: 56" D: 35.8" H: 50"	21 ft3	4	1/3 HP	White, Black, Stainless Steel
DDC 80 SS	W: 74.3" D: 35.8" H: 50"	28 ft3	4	1/3 HP	White, Black, Stainless Steel

MEAT CASES

- Large Removable Work Table
- Removable sliding doors (in rear)
- Corrosion-resistant pre-painted steel interior
- Temperature range of 32°F - 44°F
- UL, CSA and NSF Compliant

MCRU 52 W



MCRU 52WC




MCRU 100 W



MCRU 100 WL



MCSC 80 W



MODELS	Exterior Dimensions	Internal Dimensions	Shelves	Compressor power
MCRU 52 W	W: 51.3" D: 44" H: 53"	W: 47.2" D: 33" H: 21"	2	Remote
MCRU 52 WC	W: 81.2" D: 44" H: 52"	W: 76" D: 33" H: 20"	1	Remote
MCRU 100 W	W: 98.5" D: 44" H: 53"	W: 94" D: 33" H: 20"	2	Remote
MCRU 100 WL	W: 98.5" D: 44" H: 53"	W: 94" D: 33" H: 20"	2	Remote
MCSC 80 W	W: 79.2" D: 44" H: 54"	W: 74.7" D: 33" H: 21"	2	3/5 HP

REACH IN COOLERS AND FREEZERS

VRR45 2DS



VRF20 1DS



- Fully stainless steel exterior and interior cabinet
- Digital temperature control
- Polyurethane insulation for structural integrity and energy efficiency
- Casters included
- Top mount compressor
- Temperature range cooler of 34°F to 44.6°F
- Temperature range freezer of -0.4°F to -7.6°F

MODELS	Exterior Dimensions	Net Weight	Shelves	Energy Consumption	Compressor Power
VRR20 1DS	W: 26.2" D: 32.8" H: 80"	253.50 Lbs	3	4.2 kwh/24h	3/4 HP
VRR45 2DS	W: 54.4" D: 32.8" H: 80"	507 Lbs	6	6.8 kwh/24h	1/2 HP
VRF20 1DS	W: 26.2" D: 32.8" H: 80"	253.50 Lbs	3	13.9 kwh/24h	3/4 HP
VRF45 2DS	W: 54.4" D: 32.8" H: 80"	507 Lbs	6	18.66 kwh/24h	1 1/4 HP

PREP TABLES

- Digital temperature control
- Stainless steel floor, easy to clean
- Forced air refrigeration system, temperature range is 34°F to 41°F
- Casters included
- Poly-carbonate insert pans included

UCT 44 01



PPT 44 01



PPT 67 11



PPT 67 21



MODELS	Exterior Dimensions	Capacity	Shelves	Compressor Power
UCT 44 01	W: 44" D: 35" H: 40"	10.1 ft3	1	1/4 HP
PPT 44 01	W: 44" D: 35" H: 41"	10.1 ft3	1	1/4 HP
PPT 67 11	W: 67.29" D: 35" H: 41"	22.45 ft3	2	1/3 HP
PPT 67 21	W: 67.29" D: 35" H: 41"	22.45 ft3	1	1/3 HP