VERTICAL DISPLAY FREEZER MODEL: DURF32W



Product features

- Intelligent temperature control reduces energy consumption
- (8) adjustable shelves to fit your display needs
- LED lights for enhanced product display
- Self-closing, triple pane glass doors to reduce heat transfer and optimize energy savings
- Stainless steel interior floor for maximum hygiene and easy cleaning
- Evaporative condensing pan included, no plumbing required
- Automatic defrost cycle
- Forced air cascade system to promote even cooling throughout product displayed
- Illuminated display to enhance advertising opportunities



Available Color

WHITE

Accessories

- Casters
- Additional shelves

Product highlights



Electronic digital controller



Easy access to condensing unit

Certifications

LED Lighting







Warranty


- 2 year parts and labor
- Additional 3 year compressor coverage


Residential: Assumes on liabillity for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.


PRODUCT SPECIFICATIONS MODEL: DURF32W



Plan view







Technical data

Dimensions

External dimensions	W:54-11/64 " D: 27-13/64" H:78-25/64 "
Internal dimensions	W: 48-1/4" D:22-17/32 " H:59-7/32 "
Net volume	27.79 ft3 787 lts
Net weight	453.27 Lbs
Gross weight	517.64 Lbs
Shelves Dimensions	W: 23-1/2" D:20-1/4"

Performance data

Refrigerant charge	29.42 oz
Energy consumption	18.129 kw/24h
Evaporator	Forced air ventilation
Evaporation temperature	-22°F
Expansion method	Capillary
Thawing method	Electrical by resistances

Construction

Exterior material	Pre-painted sheet metal
Interior material	Pre-painted sheet metal
Number of shelves	8
Shelf material	Pre-painted sheet
Door type	Glass Door
Door quantity	2

Electrical data

Power supply	115V/ 60 Hz
Amps	7.9 A
Length of cord	74.80" (1900mm)
Lighting	LED
Plug type	NEM A 5-15 P
Controller	ERC 112
Compressor power	1 1/4 HP 844W

Cooling

Temperature range	3.2°F to 7.6°F (Exhibition)
Refrigerant	R404a
Cut In	3.2°F (-16°C)
Cut Out	-4 °F (-20°C)
Condenser	Fin-and-tube

Logistic data

Trailer Loads	29 fit on a 53' trailer
Trailer Loads	26 fit on a 48' trailer
Unit weight with packaging	517.64 Lbs
Dimensions with packaging	W: 66-17/32" D: 97-3/8" H: 92-1/8"