SPEC SHEETS

MODEL: PTP11

Pizza Prep Table

Product features

- Intelligent temperature control, optimizes and reduces energy consumption.
- Versatile arrangement, positional rack for better storage capacity.
- Food grade, floor and pans spacers in stainless steel.
- Removable cover, contains 9 polycarbonate pans, always cooled, resistant to impacts.
- Quality insulation, walls injected with high-density polyurethane.



PRO-KOLD

Available Color

Stainless steel

Product highlights



LED Lighting



Electronic digital controller



Easy access to condensing unit

Certifications







Warranty

- 2 year parts and labor
- Additional 3 year compressor coverage


Residential: Assumes on liabillity for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.


PRODUCT SPECIFICATIONS


MODEL: PTP11



Plan view







Technical data

Dimensions

| External dimensions | W:67 5/16 " D: 35" H:39 13/16" |
|---------------------|----------------------------------|
| Internal dimensions | W: 63 3/4" D:28 1/4 " H:40 3/8 " |
| Net volume | 22.42 ft3 635 Lts |
| Net weight | 433.43 Lbs |
| Gross weight | 496.04Lbs |
| Shelves Dimensions | W: 23 5/16" D:25 27/32" |
| Pans Dimensions | W: 6 7/8" D:5 7/8" H:12 3/4" |

Performance data

| Refrigerant charge | 7.41 oz |
|-------------------------|--------------------|
| Energy consumption | Not available |
| Evaporator | Forced ventilation |
| Evaporation temperature | 19.94°F |
| Expansion method | Capillary |
| Thawing method | Natural |

Construction

| Exterior material | Stainless steel |
|-------------------|-------------------------|
| Interior material | Stainless steel |
| Number of shelves | 2 |
| Shelf material | Pre-painted sheet |
| Door type | Solid (Stainless steel) |
| Door quantity | 2 |
| Pans material | Polycarbonate |
| Number of pans | 9 |

Electrical data

| Power supply | 115V/ 60 Hz |
|------------------|----------------|
| Amps | 6.1 A |
| Length of cord | 6.2 " (1900mm) |
| Lighting | LED |
| Plug type | NEMA 5-15 P |
| Controller | Not available |
| Compressor power | 1/2 HP 566W |

Cooling

| Temperature range | 33.8°F to 41°F (Exhibition) |
|-------------------|-----------------------------|
| Refrigerant | R134a |
| Cut In | 33.8°F (1°C) |
| Cut Out | 37.4 °F (3°C) |
| Condenser | Forced ventilation |
| | |

Logistic data

| Trailer Loads | 16 fit on a 53' trailer |
|----------------------------|--------------------------|
| Trailer Loads | 15 fit on a 48' trailer |
| Unit weight with packaging | 496.04Lbs |
| Dimensions with packaging | W: 72" D: 38 1/2" H: 44" |
| | |
| | |