REFRIGERATED **60" DISPLAY CASE**

MODEL: DDC60 R-290

PRO-KOLD

Product features

- Sliding glass, rear doors for effortless loading and unloading.
- Double pane, curved, front glass which reduces heat transfer and promotes product conservation
- Fully adjustable stainless steel shelves
- Stainless steel floor
- Temperature range 35.6°F to 50°F
- LED lighting for enhanced product display
- Easy access to condensing unit and easy cleaning
- **Electronic temperature controller**
- **Gravity controlled cooling system**
- 1/3 HP compressor
- R-290 ecological refrigerant that reduces and optimizes energy consumption.



Available Color

BLACK

WHITE

STAINLESS

Accessories

 Castors, lock provided on front set for more security, Castors have a diameter of 4" (102 mm).

Warranty

- 2 year parts and labor
- Additional 3 year compressor coverage

Certifications





Intertek

Intertek

Product highlights







Easy access to compressor




Electronic digital controller

Residential: Assumes on liability for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial food service or residential applications.

PRODUCT SPECIFICATIONS MODEL: DDC60 R-290



Plan view





Technical data

Dimensions

External dimensions	W: 56.69" D: 36.22" H: 46.45"
Internal dimensions	W: 53.46" D: 28.81" H: 32.67"
Net volume	15.08 ft ³ (427 L)
Net weight	335 Lb (152 kg.)
Upper Shelves Dimensions	W: 24.01" D: 18.86"
Lower Shelves Dimensions	W: 24.01" D: 22.80"

Performance data

Energy consumption	3.71 kW/24 H
Evaporator	Natural convection
Condenser	Air forced

Construction

Exterior material	Stainless steel, black and white
Interior material	Stainless Steel and White/Black metal sheet
Number of shelves storage	4
Shelf material	Stainless steel
Door type	Sliding Glass Door
Door quantity	2

Electrical data

Power supply	115 V / 60 Hz
Amps	3.72 A
Length of cord	74.80" (1900 mm)
Lighting	LED
Plug type	NEM A 5-15 P
Controller	Electronic

Cooling

Temperature range	35.6°F to 50°F (Exhibition)
Refrigerant	R-290
Refrigerant charge	3.17 oz
Cut In	39.2°F
Cut Out	35.6°F
Compressor power	1/3 HP

Logistic data

Trailer Loads	13' fit on a 48' trailer
Trailer Loads	15 fit on a 53' trailer
Unit weight with packaging	425 Lb (193 kg.)
Dimensions with packaging	W: 62.87" D: 41.5" H: 52.15"