# SELF-CONTAINED, FRESH RED MEAT DISPLAY MODEL: MCSC80W



#### **Product features**

- (2) Fully adjustable, upper shelves for additional display level
- Lower wire grill covers to keep meat off display deck and assist with proper hygiene
- Modular display case, self-contained and ready to use without internal installation
- Double pane, tempered, curved glass for maximum display view
- Counter top that facilitates customer service, weighing, or closing sales without the need for another station.
- Gravity coil cooling system in upper level to promote longevity of product.
- Adjustable feet to raise and lower box.
- (2) Rear, sliding glass doors to access display



#### **Available Color**

WHITE

#### **Accesories**

Stainless steel fish trays

## **Product highlights**







**LED Lighting** 

Sliding, rear work table

Rear, undercounter storage

#### **Certifications**





### **Warranty**


- 2 Year parts and labor
- Additional 3 year compressor coverage


Residential: Assumes on liabillity for parts or labor coverage for component failure, factory defect or any other damages for units installed in non-commercial foodservice or residential applications.

# PRODUCT SPECIFICATIONS MODEL: MCSC80W




#### **Plan view**





#### Front view



#### **Technical data**

#### **Dimensions**

External dimensions	W: 78" D: 51.5" H: 54"
Internal dimensions	W: 74.7" D: 33" H: 21.2"
Net volume	24.5 ft3 (693 L)
Net Weight	700 Lb.
Gross weight	793 Lb.
Packging dimensions	W: 85" D: 48.8" H: 55.3"

# Performance data

Refrigerant charge	Not available
Energy consumption	Not available
Compressor Power	Remote unit
Evaporation temperature	-13 °F (-25°C)
Expansion method	Expansion valve
Defrost method	Hot gas

#### Construction

Exterior material	Pre-painted sheet
Interior material	Pre-painted sheet
Number of interior shelf levels	2
Shelf material	Pre-painted steel
Door type	Sliding glass (upper), Solid (lower)
Door quantity	Upper (2), Lower (2)

#### **Electrical data**

Power supply	120 V/ 60 Hz
Amps	13 A
Length of cord	74.80" (1900 mm)
Lighting	LED
Plug type	NEM A 5-15 P
Controller	Mechanic

#### **Cooling**

Display temperature	0°C a -8°C
Display evaporator	Natural convection
Storage Temperature	-2°C a -8°C
Storage Evaporator	Forced convection
Cut In	-3°C
Cut Out	-7°C

#### **Logistic data**

Trailer Loads	12 fit on a 53' trailer
Trailer Loads	12 fit a 48' trailer
Unit weight with packaging	793 lb
Dimensions with packaging	W: 85" D: 48.8" H: 55.3"

<sup>\*</sup> W= Width, D= Depth, H= Height

<sup>\*</sup> For further information on the proper selection of the condensing unit for your display case, please identify the model of your equipment and share it with your authorized Pro-kold distributor to receive technical assistance